



## Asure Double Hung

### Without Grids

Insulated Glass Unit Package	Low E Type	Gas	Spacer System	IG Thickness	Panes of Glass	U-Factor	R-Value	Solar Heat Gain Coefficient	Visible Transmittance	UV Block
						Total Unit	Total Unit	Total Unit	Total Unit	Center of Glass
Standard	ProSolar	Argon	Intercept	3/4"	2	0.31	3.23	0.30	0.53	73%
ENERGY STAR Northern	ProSolar Sun	Argon	Super Spacer	3/4"	2	0.30	3.33	0.49	0.60	71%
ENERGY STAR North Central	ProSolar	Argon	Supercept	3/4"	2	0.30	3.33	0.30	0.53	73%
ENERGY STAR South Central	ProSolar Shade	Argon	Supercept	3/4"	2	0.29	3.45	0.21	0.49	92%
ENERGY STAR Southern	ProSolar Shade	Argon	Intercept	3/4"	2	0.30	3.33	0.21	0.49	92%

### With Grids

Insulated Glass Unit Package	Low E Type	Gas	Spacer System	IG Thickness	Panes of Glass	U-Factor	R-Value	Solar Heat Gain Coefficient	Visible Transmittance	UV Block
						Total Unit	Total Unit	Total Unit	Total Unit	Center of Glass
Standard	None	Argon	Intercept	3/4"	2	0.31	3.23	0.27	0.47	29%
ENERGY STAR Northern	ProSolar Sun	Argon	Super Spacer	3/4"	2	0.30	3.33	0.44	0.53	71%
ENERGY STAR North Central	ProSolar	Argon	Supercept	3/4"	2	0.30	3.33	0.27	0.47	73%
ENERGY STAR South Central	ProSolar Shade	Argon	Supercept	3/4"	2	0.29	3.45	0.19	0.44	92%
ENERGY STAR Southern	ProSolar Shade	Argon	Intercept	3/4"	2	0.30	3.33	0.19	0.44	92%

Please consult your Simonton Representative for additional glass package offerings.

#### Links of Interest:

[Energy-efficient Windows and Doors](#)

[Glossary of Terms](#)

<http://nffc.org>

<https://www.energystar.gov/>

<http://efficientwindows.org/understanding.php>

#### Note:

The thermal data is based on standard unit options; change in Performance Rating (DP) may require an insulating glass package upgrade.